

## TECHNICAL DATA SHEET

### V10-200


#### Eye protection

Article NO: E4003


Lens: yellow  
Material- lens: polycarbonate  
Material- temples: nylon  
Material- frame: nylon




Safety glasses with black nylon frame and black temples with yellow stripe. This glasses perfectly fit to every user thanks to adjustable length and tilt of temples. Large yellow polycarbonate lens, which are made from one piece, protect against UV radiation, filter the blue part of the light from the visible spectrum and provide greater contrast of vision in impaired light conditions. Also they are anti-fogging, anti-scratching, resistant to low-energy shocks (up to 45 m/s) at extreme temperatures (-5 °C - +55 °C) and provide maximum protection.



Adjustable temple length - YES



Adjustable temple angle - YES



Anti-fogging lens - YES



Anti-scratching lens - YES

#### Yellow lens, UV, 2-1.2 1 FT 0

Type of filter: 2 UV filter  
Shade number: 1.2 yellow  
Optical class: 1 permanent use  
Mechanical resistance: FT resistant to low-energy shocks at extreme temperatures  
Type of the lens: 0 original lens

This personal protective equipment is in conformity with these harmonized European Standards:

EN 166:2001 : Personal eye protection. General requirements.



Certified by notified body no. 0086 (BSI, Kitemark House, Maylands Avenue, Hemel Hempstead HP2 4SQ, United Kingdom),  
Certificate number 71329, dated 29<sup>th</sup> October 2010.

---

Pieces in carton:	250
Pieces in box:	10
Polybag packing (pieces):	1
Carton weight:	12 kg
Carton size:	0,103 m <sup>3</sup>

---

Store in dry and dark environment away from direct sunlight at temperatures of -5°C to +55°C, relative humidity 90% and out of sources of gasoline vapors and solvents.  
It is recommended to clean after each use. Clean at room temperature with a clean cloth, lightly moistened with a concentrated solution of water and detergent. Do not use hot water, fuel, degreasing fluids, organic solvents or abrasive cleaners.

---