

## TECHNICAL DATA SHEET

### M4200


#### Eye protection

Article NO: E4049


Lens: yellow  
Material- lens: polycarbonate  
Material- frame: polycarbonate




Extremely light and comfortable safety glasses with modern styling. Temples have soft tips, soft black aerated nose bridge ensures comfortable wear. Yellow lens are anti-fogging, anti-scratching and resistant to low-energy shocks (up to 45 m/s) at extreme temperatures (-5 °C - +55 °C).



Adjustable temple length - NO



Adjustable temple angle - NO



Anti-fogging lens - YES



Anti-scratching lens - YES

#### Clear lens, UV, 2-1.2 1 FT 0

|                        |     |  |
|------------------------|-----|--|
| Type of filter:        | 2   | solar filter   |
| Shade number:          | 1.2 | yellow   |
| Optical class:         | 1   | permanent use  |
| Mechanical resistance: | FT  | resistant to low-energy shocks at extreme temperatures |
| Type of the lens:      | 0   | original lens  |

This personal protective equipment is in conformity with these harmonized European Standards:

EN 166:2001 : Personal eye protection. General requirements.

Certified by notified body no. 0086 (BSI, Kitemark House, Maylands Avenue, Hemel Hempstead HP2 4SQ, United Kingdom),  
Certificate number 71329, dated 29<sup>th</sup> May 2012.



|                           |                      |
|---------------------------|----------------------|
| Pieces in carton:         | 250                  |
| Pieces in box:            | 10                   |
| Polybag packing (pieces): | 1                    |
| Carton weight:            | 12 kg                |
| Carton size:              | 0,105 m <sup>3</sup> |

---

Store in dry and dark environment away from direct sunlight at temperatures of -5°C to +55°C, relative humidity 90% and out of sources of gasoline vapors and solvents.

It is recommended to clean after each use. Clean at room temperature with a clean cloth, lightly moistened with a concentrated solution of water and detergent. Do not use hot water, fuel, degreasing fluids, organic solvents or abrasive cleaners.

---