

TECHNICAL DATA SHEET

M7000


Eye protection

Article NO: E4051


Lens: clear
Material - lens: polycarbonate
Material - frame: polycarbonate
Material - temples: nylon



Lightweight protective glasses with unique solution of temples. Temples are made from nylon and have a hinged system. Adjustable temple length and angle - length can be adjusted to three positions. The nose bridge is soft and ventilated. Glasses are comfortable and versatile. Clear visor is anti-fogging, anti-scratching and resistant to low-energy shocks (up to 45 m / s) even at extreme temperatures (-5 ° C - + 55 ° C).



Adjustable temple length - YES



Adjustable temple angle - YES



Anti-fogging lens - YES



Anti-scratching lens - YES

Clear lens, 2-1.2 1 FT 0

Type of the filter: 2 UV filter
Shade number: 1.2 clear lens
Optical class: 1 permanent use
Mechanical resistance: FT resistant to low-energy shocks at extreme temperatures
Type of the lens: 0 original lens



This personal protective equipment is in conformity with these harmonized European Standards:

EN 166:2001 : Personal eye protection. General requirements.

Certified by notified body no. 0086 (BSI, Kitemark House, Maylands Avenue, Hemel Hempstead HP2 4SQ, United Kingdom),
Certificate number 71329, dated 29th May 2012.

| | |
|---------------------------|----------------------|
| Pieces in carton: | 250 |
| Pieces in box: | 10 |
| Polybag packing (pieces): | 1 |
| Carton weight: | 12 kg |
| Carton size: | 0,105 m ³ |

Store in dry and dark environment away from direct sunlight at temperatures of -5°C to +55°C, relative humidity 90% and out of sources of gasoline vapors and solvents.

It is recommended to clean after each use. Clean at room temperature with a clean cloth, lightly moistened with a concentrated solution of water and detergent. Do not use hot water, fuel, degreasing fluids, organic solvents or abrasive cleaners.
