

TECHNICAL DATA SHEET

R1000


Eye protection

Article NO: E4052


Lens: double (clear and hinged welding no. 5)
Material - lens: polycarbonate
Material - frame: PVC



Safety glasses with double lenses (clear and hinged welding no. 5) and a robust frame for demanding work environments. Ventilation sidearms allows air circulation. The temples have adjustable temple angle and length (3 positions). Rubber ends of temples prevent slipping glasses in hot work environments.



Adjustable temple length - YES



Adjustable temple angle - YES



Anti-fogging lens - NO



Anti-scratching lens - NO

Clear lens, 2-1.2 1 FT 0

Type of the filter: 2 UV filter
Shade number: 1.2 clear lens
Optical class: 1 permanent use
Mechanical resistance: FT resistant to low-energy shocks at extreme temperatures
Type of the lens: 0 original lens

Smoke lens, 4-5 1 F 0 IRS

Type of the filter: 4-5 infrared filter
Optical class: 1 permanent use
Mechanical resistance: F resistant to low-energy shocks
Type of the lens: 0 original lens



IR5 - Protects against burning of the cornea during welding.

This personal protective equipment is in conformity with these harmonized European Standards:

EN 166:2001 : Personal eye protection. General requirements.

Certified by notified body no. 0086 (BSI, Kitemark House, Maylands Avenue, Hemel Hempstead HP2 4SQ, United Kingdom),
Certificate number 71329, dated 29th May 2012.

Pieces in carton:	250
Pieces in box:	10
Polybag packing (pieces):	1
Carton weight:	13 kg
Carton size:	0,105 m ³

Store in dry and dark environment away from direct sunlight at temperatures of -5°C to +55°C, relative humidity 90% and out of sources of gasoline vapors and solvents.
It is recommended to clean after each use. Clean at room temperature with a clean cloth, lightly moistened with a concentrated solution of water and detergent. Do not use hot water, fuel, degreasing fluids, organic solvents or abrasive cleaners.
