

TECHNICAL DATA SHEET

DIGGER S1 SRC

Safety shoes

Article NO: G3238

Upper: microfiber Sole: MD/rubber/TPU





Description: black-yellow color

Size: 39 - 46

Safety shoes with modern sports design. Upper is light and flexible and it is made from microfiber. There are no metal components. Ultralight toecap is made from composite.

Type and degree of protection:

Category	EN ISO 20345
Absorption of energy in the heel area	х
Sole with pattern- oil resistance x	
Antistatic properties	х
Composite safety toecap for toe protection	х
Slip resistant ceramic tile floor with SLS and on steel	
floor with glycerol (SRC)	х



This personal protective equipment is in conformity with this harmonized European Standard:

EN ISO 20345:2011 : Personal protective equipment - safety shoes. Slip resistance on ceramic tile floor with SLS and on steel floor with glycerol (SRC mark).

Certified by notified body no. 0362 (Intertek Testing Services, UK),

ARDON SAFETY s. r. o. Tržní 2902/14, Přerov I - Město Tel.: 581 250 061 www.ardon.cz



Certificate number LEC FI00370105.

Pairs in carton:	10	
Carton weight:	13,5 kg	
Carton size:	0,113 m ³	

The shoes have to be perfect as for from and size, because they have rigid parts. The right size has to be found by measuring practically and carefully the shoes. The closing system has to be used correctly. The laces have to be tightened well without leaving too long free tops. The shoes have to be cleaned and treated with right, specific products, following the instructions for use. Do not keep footwear near heatings when not used and let them dry in a windy or room temperature. Before wearing and when cleaned, the shoes have to be controlled in order to find out visible defects existing, like closing system function, outsole profile's water, possible damages, etc. To define the right type of footwear to wear in every environment, the possible dangers and the place/ environment have to be indeded (e.g. construction industry, high temperatures, etc.). The shoes have to be stored correctly, keeping them in the proper packing.