

TECHNICAL DATA SHEET DOZERLOW S3 SRC ESD

Safety shoes		
Article NO:	G3214	
Upper:	nubuck leather/textile	
Sole:	PU/ PU	
Description:	safety shoes with laminate toe cap, flexible kevlar insole	
Size:	36 - 48	

Safety shoes with laminate toe cap, flexible kevlar insole. Black colour, no metal parts. Flexible kevlar insole protects the entire area of the foot. ESD anti-static shoes protects electrostatically sensitive components from electrostatic discharges and fields.

Type and degree of protection:

Category	EN ISO 20345
Antistatic properties	х
Absorption of energy in the heel area	х
Sole with pattern- oil resistance	x
Water resistance	х
Puncture resistance (kevlar insole)	Х
Laminate safety toecap for toe protection	x
Without metal parts	x
Slip resistant ceramic tile floor with SLS and on steel floor with glycerol (SRC)	х
ESD antistatic shoes	х





This personal protective equipment is in conformity with this harmonized European Standard:

EN ISO 20345:2011 : Personal protective equipment - safety shoes.

EN ISO 61340-4-3:2001 : Electrostatics - Part 4-3: Standard test methods for specific applications - Shoes

Slip resistance on ceramic tile floor with SLS and on steel floor with glycerol (SRC mark).

Certified by notified body no. 0362 (Intertek, Centre Court, Meridian Bussiness Park, Leicester, LE19 1WD, UK) - dated 23rd November 2016, certificate no. LEC FI00365922.

Pairs in carton:	10	
Carton weight:	12,70 kg	
Carton size:	0,123 m ³	

The shoes have to be perfect as for from and size, because they have rigid parts. The right size has to be found by measuring practically and carefully the shoes. The closing system has to be used correctly. The laces have to be tightened well without leaving too long free tops. The shoes have to be cleaned and treated with right, specific products, following the instructions for use. Do not keep footwear near heatings when not used and let them dry in a windy or room temperature. Before wearing and when cleaned, the shoes have to be controlled in order to find out visible defects existing, like closing system function, outsole profile's water, possible damages, etc. To define the right type of footwear to wear in every environment, the possible dangers and the place/ environment have to be indeded (e.g. construction industry, high temperatures, etc.). The shoes have to be stored correctly, keeping them in the proper packing.