

TECHNICAL DATA SHEET

FIRSAN O1 SRA

Safety shoes

Article NO: G1187

Upper: cow leather


Liner: non-woven fabric, foam

Sole: PU2D

Description: full-leather sandal

with textile tightening

Size: 36 - 48



This shoes are suitable for use at engineering and automotive industry.

Type and degree of protection:

Category	EN ISO 20347
Antistatic properties	Х
Absorption of energy in the heel area	х
Sole with pattern- oil resistance	Х
Slip resistance on ceramic tile floor with SLS (SRA mark)	x









This personal protective equipment is in conformity with this harmonized European Standard:

EN ISO 20347:2012: Personal protective equipment - working shoes. Slip resistance on ceramic tile floor with SLS (SRA mark).

Certified by notified body no. 2369 (VIPO a.s., Slovakia) dated 31st March 2015, Certificate number 00024/111/1/2015.

Pairs in carton: 10

Carton weight: 15,7 kg Carton size: 0,089 m³



Country of origin: China

The shoes have to be perfect as for from and size, because they have rigid parts. The right size has to be found by measuring practically and carefully the shoes. The closing system has to be used correctly. The laces have to be tightened well without leaving too long free tops. The shoes have to be cleaned and treated with right, specific products, following the instructions for use. Do not keep footwear near heatings when not used and let them dry in a windy or room temperature. Before wearing and when cleaned, the shoes have to be controlled in order to find out visible defects existing, like closing system function, outsole profile's water, possible damages, etc. To define the right type of footwear to wear in every environment, the possible dangers and the place/ environment have to be indeded (e.g. construction industry, high temperatures, etc.). The shoes have to be stored correctly, keeping them in the proper packing.