

TECHNICAL DATA SHEET

TANGERSAN S1 SRC ESD

Safety shoes

Article NO: G3219

Upper: microfiber/textile

Sole: PU/ PU

Description: safety shoes with laminate

toe cap

Size: 36 - 48



Safety shoes with laminate toe cap. Dark blue colour, no metal parts. ESD anti-static shoes protects electrostatically sensitive components from electrostatic discharges and fields.

Type and degree of protection:

Category	EN ISO 20345
Antistatic properties	Х
Absorption of energy in the heel area	х
Sole with pattern- oil resistance	х
Laminate safety toecap for toe protection	x
Slip resistant ceramic tile floor with SLS and on steel floor with glycerol (SRC)	х
ESD antistatic shoes	Х













This personal protective equipment is in conformity with this harmonized European Standard:

EN ISO 20345:2011: Personal protective equipment - safety shoes.

EN ISO 61340-4-3:2001: Electrostatics - Part 4-3: Standard test methods for specific



applications - Shoes

Slip resistance on ceramic tile floor with SLS and on steel floor with glycerol (SRC mark).

Certified by notified body no. 0362 (Intertek, Centre Court, Meridian Bussiness Park, Leicester, LE19 1WD, UK) - dated 15th July 2019, certificate no. LECFI00375757.

Pairs in carton: 10
Carton weight: 9,60 kg
Carton size: 0,078 m³

The shoes have to be perfect as for from and size, because they have rigid parts. The right size has to be found by measuring practically and carefully the shoes. The closing system has to be used correctly. The laces have to be tightened well without leaving too long free tops. The shoes have to be cleaned and treated with right, specific products, following the instructions for use. Do not keep footwear near heatings when not used and let them dry in a windy or room temperature. Before wearing and when cleaned, the shoes have to be controlled in order to find out visible defects existing, like closing system function, outsole profile's water, possible damages, etc. To define the right type of footwear to wear in every environment, the possible dangers and the place/ environment have to be indeded (e.g. construction industry, high temperatures, etc.). The shoes have to be stored correctly, keeping them in the proper packing.