

DCTHI



3M THINSULATE™ LINED DOCKER GLOVE

Model DCTHI



Product specifications

Cowhide split leather with 3M Thinsulate™ lining. Canvas back with leather reinforcement. Canvas cuff.

Palm and fingers: cowhide split leather. Thickness between 1.0 and 1.2 mm.

Back: cotton fabric 200 g/m² minimum.

Cuff: cotton twill 200 g/m² minimum.

Interior: 3M Thinsulate™ thermal insulation 100 g/m² minimum.

COLOUR

Brown-Red

SIZE

10

Product Features and Benefits



3M Thinsulate™

Resistance to humidity and cold

Certifications and Standards



REGULATION (EU) 2016/425

EN420:2003+A1:2009 General requirements

EN388:2016 Protective gloves against mechanical Risks (Levels obtained on the palm)



3: Resistance to abrasion (from 1 to 4)

1: Resistance to cutting (from 1 to 5)

3: Resistance to tear (from 1 to 4)

1: Resistance to puncture (1 to 4)

X: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)



EN511:2006 Protective gloves against cold (X = Unrealized test)

1: Resistance to convective cold (from 1 to 4)

2: Resistance to contact cold (from 1 to 4)

X: Waterproof (0 or 1)

Item details

Item details	Bar code	COLOUR	SIZE		
DCTHI10	3295249019877	Brown-Red	10	60	12