

DT 1 1 9



DELTA TEK 5000 DISPOSABLE OVERALLS WITH HOOD - 4B TYPE - TAPED SEAMS

Model DT119



Product specifications

Overall with elasticated hood. 4-B type. Non-woven microporous laminate Deltatek 5000. Fastening with zip under adhesive flap (top and bottom opening). Elasticated waist and ankles. Knitted wrist. Antistatic. Single-use. Individual airtight pack.

Non woven Deltatek 5000 microporous laminate 63 g/m².

COLOUR

White

SIZE

M, L, XL, XXL

Product Features and Benefits



DELTATEK® 5000

Polyethylene film ensures better a resistance to chemical attack and better mechanical resistance (abrasion - tearing)



3-part hood

Supports head movement for increased comfort



Closure with self-adhesive flap

Very good seal



Ribbed cuffs

Good hold of the glove on the hand



Elasticated ankles



0%
SILICONE
LATEX



Microporous laminate

No risk of lint
Very soft

Waterproof seams

Decontamination work

DELTA⁵⁰⁰⁰TeK

DELTATEK 5000

Certifications and Standards



REGULATION (EU) 2016/425

EN ISO 13688:2013 General requirements for protective clothing.



EN14605:2005+A1:2009 Performance requirements for clothing with liquid-tight (Type 3) or spray-tight (Type 4) connections.

TYPE 4B: Protection against liquid chemicals (mists) - Type 4B



EN ISO 13982-1:2004+A1:2010 Protective clothing for use against solid particulates - Type 5 clothing

TYPE 5B: Protection against dust (asbestos) + biological protection Type 5B



EN13034:2005+A1:2009 Performance requirements for chemical protective clothing offering limited protective performance against liquid chemicals (Type 6 equipment)

TYPE 6B: Limited protection against liquid chemicals + biological protection Type6B



EN14126:2003+AC:2004 Protective clothing - Performance requirements and tests methods for protective clothing against infective agents



EN1073-2:2002 Protective clothing against radioactive contamination. Requirements and test methods for non-ventilated protective clothing against particulate radioactive contamination.

CLASS 1: Radioactivité - Facteur de protection 5 - Classe 1



EN1149-5:2018 Electrostatic properties - Part 5: Material performance and design requirements

:: Surface resistivity inferior or equal to 2.5×10^9 Ohms on one surface at least following EN1149-1



EN ISO 27065:2017 Performance requirements for protective clothing worn by operators applying pesticides and for re-entry workers

C1: Low exposure risk protection level against pesticides (C1).

Item details

Item details	Bar code	COLOUR	SIZE		
DT119TM	3295249103200	White	M	20	-
DT119GT	3295249103217	White	L	20	-
DT119XG	3295249103224	White	XL	20	-
DT119XX	3295249103231	White	XXL	20	-