

DT250



ONE-PIECE DISPOSABLE OVERALL WITH HOOD - 4B TYPE - TAPED SEAMS

Model DT250



#### Product specifications

Overall with integrated feet with non-slip soles and elasticated hood. 4-B type. PE/PP non woven. Fastening with zip under flap. Elasticated around the head, waist, cuffs and ankles. Single-use. Individual airtight pack.

Non woven PE/PP.

#### COLOUR

White

#### SIZE

M, L, XL, XXL, 3XL

Product Features and Benefits

Waterproof seams

Decontamination work



Closure with chin strap

Very good support and reinforced protection



Double thumb loops

Very good support



Adhesive tape to connect a glove

Total water-proofing



PE/PP material

No risk of lint

## Certifications and Standards



REGULATION (EU) 2016/425

EN ISO 13688:2013 General requirements for protective clothing.



EN14605:2005+A1:2009 Performance requirements for clothing with liquid-tight (Type 3) or spray-tight (Type 4) connections.

TYPE 4B: Protection against liquid chemicals (mists) - Type 4B



EN ISO 13982-1:2004+A1:2010 Protective clothing for use against solid particulates - Type 5 clothing

TYPE 5B: Protection against dust (asbestos) + biological protection Type 5B



EN13034:2005+A1:2009 Performance requirements for chemical protective clothing offering limited protective performance against liquid chemicals (Type 6 equipment)

TYPE 6B: Limited protection against liquid chemicals + biological protection Type6B



EN14126:2003+AC:2004 Protective clothing - Performance requirements and tests methods for protective clothing against infective agents



EN1073-2:2002 Protective clothing against radioactive contamination. Requirements and test methods for non-ventilated protective clothing against particulate radioactive contamination.

CLASS 1: Radioactivité - Facteur de protection 5 - Classe 1

## Item details

Item details	Bar code	COLOUR	SIZE		
DT250TM	3295249214883	White	M	20	-
DT250GT	3295249214890	White	L	20	-
DT250XG	3295249214906	White	XL	20	-
DT250XX	3295249214913	White	XXL	20	-
DT2503X	3295249214920	White	3XL	20	-