

DT300 DELTACHEM



DELTACHEM DISPOSABLE OVERALLS WITH HOOD - 3B TYPE - TAPED SEAMS

Model DT300



Product specifications

Overall with three-sided elasticated hood. 3-B type. Non woven Deltachem. Zip Fastening under double flap. Double elastic for thumb. Elasticated around the head, waist, cuffs and ankles. Single-use. Individual airtight pack.

DELTACHEM nonwoven 5 layers.
SMS with double outer chemical barrier 82 g/m².

COLOUR

Yellow

SIZE

M, L, XL, XXL

Product Features and Benefits



DELTACHEM

Enhanced protection against chemicals
No risk of lint



3-part hood

Supports head movement for increased comfort



Waterproof seams

Decontamination work



Closure with double flap

Total water-proofing



Double thumb loops

Good hold of the glove on the hand



Elasticated ankles

More comfort



Certifications and Standards



REGULATION (EU) 2016/425

EN ISO 13688:2013 General requirements for protective clothing.



EN14605:2005+A1:2009 Performance requirements for clothing with liquid-tight (Type 3) or spray-tight (Type 4) connections.

TYPE 3B: Protection against liquid chemicals + biological protection - Type 3B (jets)
TYPE 4B: Protection against liquid chemicals (mists) - Type 4B



EN ISO 13982-1:2004+A1:2010 Protective clothing for use against solid particulates - Type 5 clothing

TYPE 5B: Protection against dust (asbestos) + biological protection Type 5B



EN13034:2005+A1:2009 Performance requirements for chemical protective clothing offering limited protective performance against liquid chemicals (Type 6 equipment)

TYPE 6B: Limited protection against liquid chemicals + biological protection Type 6B



EN14126:2003+AC:2004 Protective clothing - Performance requirements and tests methods for protective clothing against infective agents



EN1073-2:2002 Protective clothing against radioactive contamination. Requirements and test methods for non-ventilated protective clothing against particulate radioactive contamination.

CLASS 1: Radioactivité - Facteur de protection 5 - Classe 1



EN1149-5:2018 Electrostatic properties - Part 5: Material performance and design requirements

Item details

Item details	Bar code	COLOUR	SIZE		
DT300TM	3295249192914	Yellow	M	20	-
DT300GT	3295249192907	Yellow	L	20	-
DT300XG	3295249192921	Yellow	XL	20	-
DT300XX	3295249192938	Yellow	XXL	20	-