

PVC7335



PVC GLOVE - LENGTH 35 CM

Model PVC7335



#### Product specifications

PVC on interlock cotton lining. Length: 35 cm. Thickness 0,90 mm.

Support: interlock cotton.

Coating: 100% cured and vulcanised PVC.

#### COLOUR

Red

#### SIZE

10

#### Product Use - Risks



Biological



Wearing



Chemical



Particules

**CHEM D-FINDER** 

Certifications and Standards



REGULATION (EU) 2016/425

EN ISO 21420:2020 General requirements

EN388:2016+A1:2018 Protective gloves against mechanical Risks (Levels obtained on the palm)



- 2: Resistance to abrasion (from 1 to 4)
- 1: Resistance to cutting (from 1 to 5)
- 2: Resistance to tear (from 1 to 4)
- 1: Resistance to puncture (1 to 4)
- X: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)

EN ISO 374-1:2016+A1:2018 Protective gloves against dangerous chemicals and micro-organisms - Part 1: Terminology and performance requirements for chemical risks.



- TYPE C: Type C - Water and air tightness according to EN ISO 374-2:2019. Permeation resistance to at least 1 chemicals at level 1 according to EN16523-1: 2015 (from 1 to 6).
- ..: Determination of resistance to degradation by chemicals according to EN ISO 374-4: 2019. Part 4: Determination of resistance to degradation by chemicals.
- K 6 > 480 mn: Caustic soda 40% (K) CAS 1310-73-2

EN ISO 374-5:2016 Protective gloves against dangerous chemicals and micro-organisms - Part 5: Terminology and performance requirements against micro- organisms risks.



- BACTERIA + FUNGI ..: BACTERIA + FUNGI : Water and air tightness according to EN ISO 374-2:2019.

Item details

Item details	Bar code	COLOUR	SIZE		
PVC733510	3295249020200	Red	10	120	12