

# BALI S3

3H149EV

CE UNI EN ISO 20345:2012 S3 SRC ESD

High shoe, WRU anti-scratch back leather thickness 1,8-2,0 mm.  
Highly perspiring and abrasion resistant fabric lining.  
Reinforced heel area STABILITY SUPPORT in PU.  
Soft, lined and padded tongue.

## COMPLETELY METAL FREE SHOE

The shoe satisfies the requirements of slipping resistance on inclined roofs according to **UNI 11583:2015**

**TOECAP 200J** polymeric **composite non-thermic** according to EN 12568

**MIDSOLE flexible antiperforation composite fabric** according to EN 12568

**SOLE 3HYBRID** three-densities polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

**ANTI TORSION** insert in the sole to assure stability on uneven ground

**INSOLE 5000, three-materials extracomfort:** perspiring, removable, anatomic, absorbing, ESD and anti-bacterial

The shoes satisfies the requirement according to the norm IEC 61340-4-3:2017 (IEC 61340-5-1:2016) for the electrical resistance **ESD**

**Size 36-47 Shoe weight Sz 42 gr. 550**




## CERTIFICATIONS



## TECHNOLOGIES AND MATERIALS



## SECTORS



## SOLE



3Hybrid is a revolutionary line that thanks to the design of the sole ensures maximum shock absorber and energy return during the entire useful life of the shoe. 3Hybrid belongs to the 3D generation. This shoe is therefore equipped with 3 different layers of sole with relative densities, each specialized to maximize comfort, anti-slip and foot stability. The whole collection is also equipped with an anti-torsion insert to ensure additional support for the foot at every step.

## PLUS



### ZERO ABRASION

The Zero Abrasion technology is an anti-scratch leather, finished with a polyurethane multi-layer, that assures a complete protection of the upper against usury and abrasion. Highly resistant to water and oils, this leather is suitable for people who like wearing always clean and nice shoes even after months of usage.



### STABILITY SUPPORT

Stability Support is the Giasco technology that guarantees the maximum heel support during walking. Inside it there's a particular structure that localizes the support only on specific areas, in order to avoid an excessive stress of the foot. It helps the correct walking and a better discharge of the weight along all the foot, with advantaged for back and joints.



### ANTI TORSION

The usage of the anti-torsion shank is finalized to give to the shoe extreme stability on every ground. Mostly indicated for the building sector, where the risks caused by uneven and wet grounds are higher, this technology is very useful for people working on ladders (painters, windows' cleaners, bricklayers) as it increases the stability in the central part of the plant, the mostly stanced area on the ladder. It limits the heel stress and helps plant arch and ankle.



### 3D TRIPLA DENSITA' INIETTATA

3D is a revolutionary certified technology that offers the only shoe with three different layers of polyurethane injected. The most external section, with hard mix, offers the maximum resistance for the surface contact and perfect SRC performances. The middle part, with a softer mix, assures comfort when walking. The higher section, next to the upper, guarantees better stability to the foot. Three densities and the combination of three colors are the special characteristics of this new shoes generation.