

CROSS S1P HRO

4X141T

CE UNI EN ISO 20345:2012 S1P HRO SRC

Low, holed shoe, suede back leather thickness 1,8-2,0 mm.
Heel area with WRU anti-scratch back leather thickness 1,8-2,0 mm.
Highly perspiring and abrasion resistant fabric lining.
Shoe with refracting fabric insert.
Soft, lined and padded tongue.

COMPLETELY METAL FREE SHOE

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE RUBBER 4X4 ANTISTATIC bidensity: polyurethane and antistatic **RUBBER**. Sole resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC HRO** resistance to hot contact of the outsole

INSOLE 5000, three-materials extracomfort: perspiring, removable, anatomic, absorbing, ESD and antibacterial

Size 39-47 Shoe weight Sz 42 gr. 545



CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS



SOLE



4X4 is the PU/Rubber line studied for the working places where extreme temperatures are a danger for shoes resistance and consequently for workers. For this reason the specific compound of the outsole is studied to assure a complete protection from -17°C until 300°C. At the same time the expanded midsole assures the best comfort while walking, thanks to its low density.

PLUS



ZERO ABRASION

The Zero Abrasion technology is an anti-scratch leather, finished with a polyurethane multi-layer, that assures a complete protection of the upper against usury and abrasion. Highly resistant to water and oils, this leather is suitable for people who like wearing always clean and nice shoes even after months of usage.

ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS			
SRC			
ANTISLIPPING TEST			
SRA	HEEL=0,38	0,85	
FLAT=0,32	0,85		
SMB	HEEL=0,43	0,25	
FLAT=0,38	0,25		