

CUBA S3

AC049D

CE UNI EN ISO 20345:2012 S3 SRC

High shoe, WRU back leather and WRU suede back leather thickness 1,8-2,0 mm.

Perspiring and abrasion resistant fabric lining.

Soft, lined and padded tongue.

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE ACTION bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE 5000, three-materials extracomfort: perspiring, removable, anatomic, absorbing, ESD and anti-bacterial.

Size 36-47 Shoe weight Sz 42 gr. 650



CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS



FARMING AND MINING



COMPONENTS AND AUTOMOTIVE



WOOD

METAL CARPENTRY



BUILDING AND HEAVY INDUSTRY



LOGISTICS AND LIGHT INDUSTRY

SOLE



Action is a shoe studied for external jobs, with soft lines making it very light and comfortable.

PLUS

ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS			
SRC			
SRA	HEEL >= 0,28	0,39	
PLATEAU	PLATEAU >= 0,20	0,39	
SMB	HEEL >= 0,23	0,39	
PLATEAU	PLATEAU >= 0,18	0,39	