

DAKOTA S3 CI

TO011D

CE UNI EN ISO 20345:2012 S3 CI SRC

Calf boot, WRU water resistant leather and WRU anti-scratch back leather thickness 1,8-2,0 mm.

Perspiring and abrasion resistant fabric lining.

Boot with refracting fabric insert.

COMPLETELY METAL FREE BOOT

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE flexible **antiperforation composite fabric** according to EN 12568

SOLE STABILE bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE 5000, three-materials extracomfort: perspiring, removable, anatomic, absorbing, ESD and anti-bacterial

CI insulated surface against cold -17°C

Boot height sole included 28,5 cm

Size 39-47 Boot weight Sz 42 gr. 770



CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS



FARMING AND MINING



BUILDING AND HEAVY INDUSTRY



COLD

PLACES



OIL AND GAS

SOLE



Stabile is the comfortable alternative to the classic and "heavy" shoe for building sector. This sole is highly performing with specific dowels, with dimensions and shapes to assure the maximum stability, with self-cleaning drainage channels to assure a perfect cleaning and with a soft compound to isolate the foot to the continuous shocks. Line studied with a lot of attention to the technology of uppers and lightness of the materials.

PLUS



ZERO ABRASION

The Zero Abrasion technology is an anti-scratch leather, finished with a polyurethane multi-layer, that assures a complete protection of the upper against usury and abrasion. Highly resistant to water and oils, this leather is suitable for people who like wearing always clean and nice shoes even after months of usage.

ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS			
SRC			
ANTISLIPPING INDEX			
DATA	HEEL	HEEL	HEEL
SRP	SRP	SRP	SRP
SRP	SRP	SRP	SRP
SRP	SRP	SRP	SRP
SRP	SRP	SRP	SRP