



GYM S3

73N37C

CE UNI EN ISO 20345:2012 S3 SRC ESD CLASS 3

High shoe, IDROTECH® WRU grain Nubuck leather thickness

Perspiring and resistant to abrasion fabric lining.

Shoe with refracting fabric insert.

Soft, lined and padded tongue.

COMPLETELY METAL FREE SHOE

TOECAP 200J polymeric composite non-thermic according to EN

MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE ERGO SAFE bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, antishock and anti-slipping SRC

INSOLE 5000, three-materials extracomfort: perspiring, removable, anatomic, absorbing, ESD and anti-bacterial The shoe satisfies the requirement according to the norm EN ISO 61340-4-3:2001 for the electrical resistance ESD class 3 (electric dissipative footwear)

Size 36-47 Shoe weight Sz 42 gr. 540



CERTIFICATIONS











TECHNOLOGIES AND MATERIALS















SECTORS



COMPONENTS AND AUTOMOTIVE



WOOD METAL CARPENTRY



LOGISTICS AND LIGHT INDUSTRY



ESD AREAS

SOLE



Ergo Safe is the safety shoe useful for people who have problems with back and joint pains. It is in fact the only ergonomic shoe in the market, studied to give a solution to these needs and in the same time to assure a complete protection. This is possible thanks to the round sole, that allows a uniform discharge of body weight all along the sole of the foot, giving a good feeling to the back, the knees and to the heels. Ergo is also studied to improve walking, by giving a better blood circulation and a saving of energy at the end of

PLUS



IDROTECH®

IDROTECH® is a leather treatment with the aim to optimize the water resistance and the foot perspiration. This particular tunning method, thanks to the used mineral salts, gives an excellent softness and a complete mechanical resistance to oils and hydrocarbons. The IDROTECH \$ leather is certified according to the norms ISO 4045, ISO 17075 and ISO 5403.

ANTISLIPPING TEST RESULTS

