

IRON RM S3

AC068DRM

CE UNI EN ISO 20345:2012 S3 M SRC

High shoe, WRU back leather thickness 1,8-2,0 mm.

Perspiring and abrasion resistant fabric lining

Shoe with refracting insert.

Soft, lined and padded tongue.

Shoe with fast device.

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE ACTION bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE 4000, removable, anatomic, absorbing, antistatic and perspiring

M metatarsal protection

Size 37-47 Shoe weight Sz 42 gr. 650




CERTIFICATIONS




TECHNOLOGIES AND MATERIALS



SECTORS

 FARMING AND MINING

 BUILDING AND HEAVY INDUSTRY

SOLE



Action is a shoe studied for external jobs, with soft lines making it very light and comfortable.

PLUS

ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS

SRC		SRC	
SHOES	HEEL	HEEL	HEEL
SHOES	HEEL=0,38	HEEL=0,38	HEEL=0,38
SHOES	PLATE=0,38	PLATE=0,38	PLATE=0,38
SHOES	HEEL=0,38	HEEL=0,38	HEEL=0,38
SHOES	PLATE=0,38	PLATE=0,38	PLATE=0,38