

# KENT S3

AC061D

CE UNI EN ISO 20345:2012 S3 SRC

Low shoe, WRU back leather thickness 1,8-2,0 mm.  
Perspiring and abrasion resistant fabric lining.  
Shoe with refracting fabric insert.  
Soft, lined and padded tongue.

**TOECAP 200J** polymeric **composite non-thermic** according to EN 12568

**MIDSOLE flexible antiperforation composite fabric** according to EN 12568

**SOLE ACTION** bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

**INSOLE 4000**, removable, anatomic, absorbing, antistatic and perspiring.

**Size 36-51 Shoe weight Tg 42 gr. 595**




## CERTIFICATIONS



## TECHNOLOGIES AND MATERIALS



## SECTORS



## SOLE



Action is a shoe studied for external jobs, with soft lines making it very light and comfortable.

## PLUS

## ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS			
<b>SRC</b>			
SRA	HEEL >= 0,28	0,39	
FOUR	PLATE >= 0,28	0,39	
SMB	HEEL >= 0,23	0,39	
FOUR	PLATE >= 0,23	0,39	