

# LIPARI S1P

3H182NG

CE UNI EN ISO 20345:2012 S1P SRC

Low holed shoe, MICRO-tech technical fabric thickness 1,8-2,0 mm. Highly perspiring and abrasion resistant fabric lining. Shoe with refracting fabric insert. Soft and lined tongue. COMPLETELY METAL FREE SHOE

**TOECAP 200J** polymeric **composite non-thermic** according to EN 12568

MIDSOLE flexible antiperforation composite fabric according to EN 12568

**SOLE 3HYBRID** three-densities polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC** 

**ANTI TORSION** insert in the sole to assure stability on uneven ground

**INSOLE 5000**, three-materials extracomfort: perspiring, removable, anatomic, absorbing, ESD and anti-bacterial

Size 36-47 Shoe weight Sz 42 gr. 485



## CERTIFICATIONS



## **TECHNOLOGIES AND MATERIALS**



## SECTORS

COMPONENTS AND AUTOMOTIVE

WOOD METAL CARPENTRY



### SOLE



3Hybrid is a revolutionary line that thanks to the design of the sole ensures maximum shock absorber and energy return during the entire useful life of the shoe. 3Hybrid belongs to the 3D generation. This shoe is therefore equipped with 3 different layers of sole with relative densities, each specialized to maximize comfort, anti-slip and foot stability. The whole collection is also equipped with an anti-torsion insert to ensure additional support for the foot at every step.

## PLUS



3PU PATEN

#### ANTI TORSION

The usage of the anti-torsion shank is finalized to give to the shoe extreme stability on every ground. Mostly indicated for the building sector, where the risks caused by uneven and wet grounds are higher, this technology is very useful for people working on ladders (painters, windows' cleaners, bricklayers) as it increases the stability in the central part of the plant, the mostly standed area on the ladder. It limits the heel stress and helps plant arch and ankle.

#### **3D TRIPLA DENSITA' INIETTATA**

3D is a revolutionary certified technology that offers the only shoe with three different layers of polyurethane injected. The most external section, with hard mix, offers the maximum resistance for the surface contact and perfect SRC performances. The middle part, with a softer mix, assures comfort when walking. The higher section, next to the upper, guarantees better stability to the foot. Three densities and the combination of three colors are the special characteristics of this new shoes generation.

