

MALAGA S3

TO061D

CE UNI EN ISO 20345:2012 S3 SRC

Low shoe, WRU back leather thickness 1,8-2,0 mm.
Perspiring and abrasion resistant fabric lining.
Shoe with refracting fabric insert.
Soft, lined and padded tongue.

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE STABILE bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE 4000, removable, anatomic, absorbing, antistatic and perspiring

Size 39-47 Shoe weight Sz 42 gr. 610



CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS



FARMING AND MINING



WOOD METAL CARPENTRY



BUILDING AND

HEAVY INDUSTRY

SOLE



Stabile is the comfortable alternative to the classic and "heavy" shoe for building sector. This sole is highly performing with specific dowels, with dimensions and shapes to assure the maximum stability, with self-cleaning drainage channels to assure a perfect cleaning and with a soft compound to isolate the foot to the continuous shocks. Line studied with a lot of attention to the technology of uppers and lightness of the materials.

PLUS

ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS			
SRC			
SRA	HHEEL>= 0,30	0,45	
PLAT>= 0,30	0,44		
SRB	HHEEL>= 0,30	0,39	
PLAT>= 0,30	0,38		