

OXFORD S3

KU068D

CE UNI EN ISO 20345:2012 S3 SRC

High shoe, back WRU leather thickness 1,8-2,0 mm.

Perspiring and abrasion resistant fabric lining.

Shoes with refracting fabric insert.

Soft, lined and padded tongue.

The shoe satisfies the requirements of slipping resistance on inclined roofs according to **UNI 11583:2015**

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE KUBE bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92,

to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE 4000, removable, anatomic, absorbing, antistatic and perspiring

Size 35-49 Shoe weight Sz 42 gr. 550



CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS



SOLE



In order to avoid the high number of accidents caused by slipping danger, Giasco realized an excellent anti-slipping product. This sole is called Kube, a young and sporty styled shoe equipped with a special gripping compound and specific cubic dowels with inverted profile in the outsole. With thanks to these special characteristics Kube obtained the maximum certification against slipping: jobs on inclined roofs (UNI 11583:2015).

PLUS

ANTISLIPPING TEST RESULTS

| ANTISLIPPING TEST RESULTS | | | |
|---------------------------|-------------|------|--|
| SRC | | | |
| ANTISLIPPING TEST | | | |
| SRX | HEEL x 0,20 | 0,40 | |
| SRX | HEEL x 0,20 | 0,40 | |
| SRX | HEEL x 0,20 | 0,40 | |
| SRX | HEEL x 0,20 | 0,40 | |
| SRX | HEEL x 0,20 | 0,40 | |