

# SALVADOR S3

AC003D

CE UNI EN ISO 20345:2012 S3 SRC

Low shoe, WRU back leather and WRU suede back leather thickness 1,8-2,0 mm.

Perspiring and abrasion resistant fabric lining.

Soft, lined and padded tongue.

**TOECAP 200J** polymeric **composite non-thermic** according to EN 12568

**MIDSOLE flexible antiperforation composite fabric** according to EN 12568

**SOLE ACTION** bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

**INSOLE 5000, three-materials extracomfort:** perspiring, removable, anatomic, absorbing, ESD and anti-bacterial

**Size 39-47 Shoe weight Sz 42 gr. 550**



## CERTIFICATIONS



## TECHNOLOGIES AND MATERIALS



## SECTORS



COMPONENTS AND AUTOMOTIVE



WOOD METAL CARPENTRY



BUILDING AND HEAVY INDUSTRY



LOGISTICS AND LIGHT INDUSTRY

## SOLE



Action is a shoe studied for external jobs, with soft lines making it very light and comfortable.

## PLUS

## ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS			
SRC			
ANTISLIPPING TEST			
DATA	MEASUREMENT	RESULT	CLASS
SRP	MEASUREMENT	0.38	0.38
SRP	MEASUREMENT	0.38	0.38
SRP	MEASUREMENT	0.38	0.38
SRP	MEASUREMENT	0.38	0.38