

SNAKE 02 FO

C71810

CE UNI EN ISO 20347:2012 O2 FO SRC ESD

Low shoe, MICROWASH thickness 1,8-2,0 mm.
Perspiring and abrasion resistant fabric lining.

COMPLETELY METAL FREE SHOE

SOLE CITY bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE 5000, three-materials extracomfort: perspiring, removable, anatomic, absorbing, ESD and anti-bacterial

FO sole resistance to hydrocarbons

The shoe satisfies the requirement according to the norm IEC 61340-4-3:2017 (IEC 61340-5-1:2016) for the electrical resistance

ESD

Size 36-47 Shoe weight Sz 42 gr. 440



CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS



SOLE



City is a unique styled shoe, perfect for people who look for a safety shoe to use in a lot of different situations, free time included. Giasco developed for this product a special gel insert in the heel zone, called G-GEL, useful to reduce the impact stress et to release energy during walking. This sole has been studied with a special attention to the design of uppers and sole and to the technology of hidden outsole.

PLUS



MICROWASH

MICRO WASH is a Chrome free material finished with perspiring polyurethanes. Very light and perspiring, it is suitable for alimentary et hospital sectors. It is also studied for people wearing the shoes for a lot of hours on wet surfaces. It resists to acids, mostly oleic acid. It is washable with water and neutral soap at 40°.

ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS			
SRC			
ANTISLIPPING INDEX			
SRA	HEEL=0,52	0,52	0,52
PLATE=0,52	PLATE=0,52	0,52	0,52
SMB	HEEL=0,52	0,52	0,52
PLATE=0,52	PLATE=0,52	0,52	0,52