

# SOLDADOR S3

AC880BSP

CE UNI EN ISO 20345:2012 S3 SRC

High shoe, water-resistant WRU leather thickness 1,8-2,0 mm.  
Perspiring and abrasion resistant fabric lining.  
High visibility fabric insert. Lined and padded tongue.  
Shoe with dross protective leather cover tongue and side closing by click buckle.

**TOECAP 200J** polymeric **composite non-thermic** according to EN 12568

**MIDSOLE antiperforation steel** according to EN 12568

**SOLE ACTION** bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

**INSOLE 1000**, in high density and open cells latex foam.

Absorbing, antistatic and perspiring

**Size 39-47 Shoe weight Sz 42 gr. 635**




## CERTIFICATIONS



## TECHNOLOGIES AND MATERIALS



## SECTORS

 WOOD METAL CARPENTRY

 BUILDING AND HEAVY INDUSTRY



WELDER

## SOLE



Action is a shoe studied for external jobs, with soft lines making it very light and comfortable.

## PLUS

## ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS

**SRC**

SHOES	HEEL	SOLE
SRA	HEEL >= 0,38	0,38
	PLATE >= 0,32	0,38
SRB	HEEL >= 0,23	0,28
	PLATE >= 0,18	0,28