

# SPIDER O1P FO

C7154N

CE UNI EN ISO 20347:2012 O1P FO SRC ESD

Low shoe, technical fabric micro-tech thickness 1,8-2,0 mm., with 3D external fabric, perspiring and resistant to abrasion. Perspiring and abrasion resistant fabric lining. Shoe with refracting fabric insert. Soft, lined and padded tongue.

**COMPLETELY METAL FREE SHOE**

**MIDSOLE flexible antiperforation composite fabric** according to EN 12568

**SOLE CITY** bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

**INSOLE 5000, three-materials extracomfort:** perspiring, removable, anatomic, absorbing, ESD and anti-bacterial

The shoe satisfies the requirement according to the norm IEC 61340-4-3:2017 (IEC 61340-5-1:2016) for the electrical resistance **ESD**

**Size 36-47 Shoe weight Sz 42 gr. 460**



**CERTIFICATIONS**



**TECHNOLOGIES AND MATERIALS**



**SECTORS**

-  LOGISTICS AND LIGHT INDUSTRY
-  ESD AREAS
-  FOOD, HOSPITAL
-  HOTELS, RESTAURANTS & CATERING
-  AND HYGIENE

**SOLE**



City is a unique styled shoe, perfect for people who look for a safety shoe to use in a lot of different situations, free time included. Giasco developed for this product a special gel insert in the heel zone, called G-GEL, useful to reduce the impact stress et to release energy during walking. This sole has been studied with a special attention to the design of uppers and sole and to the technology of hidden outsole.

**PLUS**

**ANTISLIPPING TEST RESULTS**

| ANTISLIPPING TEST RESULTS |           |      |  |
|---------------------------|-----------|------|--|
| <b>SRC</b>                |           |      |  |
| ANTISLIPPING INDEX        |           |      |  |
| SRA                       | HEEL=0,42 | 0,52 |  |
| PLATE=0,38                | 0,52      |      |  |
| SMB                       | HEEL=0,33 | 0,38 |  |
| PLATE=0,38                | 0,38      |      |  |