

TENNIS S1P

ER172T

CE UNI EN ISO 20345:2012 S1P SRC

Low shoe, perspiring and abrasion resistant technical fabric with silkscreen printing and MICROWASH thickness 1,8-2,0 mm.
Highly perspiring and abrasion resistant fabric lining.
Soft, lined and padded tongue.

COMPLETELY METAL FREE SHOE

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE ERGO SAFE bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE 5000, three-materials extracomfort: perspiring, removable, anatomic, absorbing, ESD and anti-bacterial

Size 36-47 Shoe weight Sz 42 gr. 480



CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS



SOLE



Ergo Safe is the safety shoe useful for people who have problems with back and joint pains. It is in fact the only ergonomic shoe in the market, studied to give a solution to these needs and in the same time to assure a complete protection. This is possible thanks to the round sole, that allows a uniform discharge of body weight all along the sole of the foot, giving a good feeling to the back, the knees and to the heels. Ergo is also studied to improve walking, by giving a better blood circulation and a saving of energy at the end of the day.

PLUS



MICROWASH

MICRO WASH is a Chrome free material finished with perspiring polyurethanes. Very light and perspiring, it is suitable for alimentary et hospital sectors. It is also studied for people wearing the shoes for a lot of hours on wet surfaces. It resists to acids, mostly oleic acid. It is washable with water and neutral soap at 40°.

ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS

SRC		
SRA	HEEL >= 0,28	0,31
SRP	HEEL >= 0,28	0,31
SMB	HEEL >= 0,23	0,22
SRW	HEEL >= 0,28	0,22