

# TECHNICAL SPECIFICATION

RESPIRATORY PROTECTION



## F600 SERIES

### F621 - FFP2 - VERTICAL FOLD FLAT DISPOSABLE DUST MASK

Product Code: BGV120-000-Q00



#### Description

Vertical fold flat respirator with foam padded adjustable nose clip

#### Options

Box of 40 code: BGV120-000-Q00



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.  
Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jgpsafety.com / Web: www.jgpsafety.com  
Do Not Publish without written permission from JSP Limited. Contact copyright@jgpsafety.com.  
Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.  
Page 1 of 3 / Issued 30 Oct 2020 / Copyright 2018 - 2020. JSP Limited. All Rights Reserved.



[www.jgpsafety.com](http://www.jgpsafety.com)

[sales@jgpsafety.com](mailto:sales@jgpsafety.com)


UK tel: +44 (0)1993 826050

## FEATURES



### FOLDS FLAT

Fold flat design is compact and easy to carry in a pocket



### FOAM PADDED NOSE BRIDGE,

A mouldable nose bridge and foam pad on the inside for comfort and a firmer fit



### 4-POINT ADJUSTABLE STRAPS,

Metal free, 4-point headband adjustable straps create a firm and adaptable fit

## COMPATIBLE PRODUCTS

EVO® Gas Goggle  
EVO® Goggle Double Lens  
EVO® Goggle Single Lens  
Sonis® Compact Ear Defenders  
Sonis®1 Ear Defenders  
Sonis®2 Ear Defenders  
Sonis®3 Ear Defenders  
Stealth™ 16G  
Stealth™ 7000  
Stealth™ 8000  
Stealth™ 9000  
Stealth™ Coverlite™ Overspec  
Thermex™ Double Lens Goggle

## ACCESSORIES

Portacount/AccuFIT Quantitative/Qualitative Face Fit Testing Kit & Spares

## SAFETY STANDARDS

EN 149:2001 + A1:2009

CE 0370-4691-PPE/B issued by APPLUS

## SPECIFICATIONS

Classification

FFP2 (Filtering Facepiece Particulate)

Filter Type

P (Protects Against Solid and Liquid Aerosols)

Usage

NR (Non-Reusable)

Activated Carbon Layer



No

Minimum Filtration Efficiency



94% For FFP2 Rated

Maximum Total Inward Leakage (TIL)

8%

Nominal Protection Factor (NPF)

12

UK Assigned Protection Factor (APF)

10

Mask Design

Vertical Fold Flat



Exhalation Valve

No

4-Point Headband Adjustable Straps

Yes



Nose Bridge

Moulded in mask

Mask Material

Polypropylene

Filter Shelf Life

5 Years



Product Weight

16g (Approx)

## APPLICATIONS

- Mining, Aggregates and Quarrying
- Agriculture
- Forestry & Landscaping
- Manufacturing
- Construction & Infrastructure
- Scaffolding & Roofing
- Welding (mild)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com.

Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 30 Oct 2020 / Copyright 2018 - 2020. JSP Limited. All Rights Reserved.



## INSTRUCTIONS FOR USE

- Mask must be fitted in accordance with the instructions supplied
- Care must be taken to ensure that the correct mask type is selected for the work to be carried out
- If in doubt as to the type of mask required, seek professional guidance

## CLEANING & MAINTENANCE

- Not Applicable - Disposable Product
- Store the masks out of sunlight away from chemicals in a dry atmosphere

## DIMENSIONS OF MASK

- Depth: 12.5cm / Width: 15cm

## DIMENSIONS OF BOX

- Depth: 13cm / Width: 13cm / Height: 21cm

## DIMENSIONS OF OUTER PACKAGING

- Quantity: 1,200 (30 inner packs of 40 masks)
- Depth: 670mm / Width: 410mm / Height: 440mm

## LIMITATIONS OF USE

- Protection will only be offered if the mask is fitted correctly
- The mask, when in contact with the skin may cause allergic
- Do not use where exposure to chemical gases may be experienced
- Use in well ventilated areas only, which are not deficient in oxygen and do not contain explosive atmospheres
- Ensure good seal around the face is created before entering the hazard area
- The working life of the mask is nominally one day (this is based on a working day shift of 8 hours), however it may be affected by many factors, including work rate, airflow and concentration of any contaminant in the atmosphere. The mask should be changed immediately if,
  - a.) Breathing difficulties due to clogging are experienced,
  - b.) Breakthrough of a contaminant is detected by smell, taste or any other means, or
  - c.) The mask becomes damaged

