

Product Datasheet uvex 1 sport nc 6595.7-9 O1 FO SRC

**UVEX ARBEITSSCHUTZ GmbH, Würzburger Str. 181-189, D-90766 Fürth**

| | |
|----------------------------|---|
| General Features | <ul style="list-style-type: none">• Modern, ultralightweight and flexible O1 occupational shoe without toecap• Breathable textile upper material• Suitable for people allergic to chrome as it's made from synthetic materials• All sole materials are free of silicones, plasticisers and other paint wetting impairment substances |
| Protection features | <ul style="list-style-type: none">• Meets the ESD specification with volume resistance less than 35 megaohms• Ergonomically designed outsole comprising dual-density polyurethane with excellent slip resistant |
| Comfort features | <ul style="list-style-type: none">• Virtually seam-free construction made from high-tech materials to eliminate pressure points• Weich gepolsterte Lasche und Kragen• Outstanding wearer comfort results from a newly developed last and climate-optimised, breathable materials• Removeable anti-static comfortable insole, with a moisture transport system and additional shock absorption around the heel and forefoot• uvex climazone technology for optimum comfort• sizes 35-40 are produced using a women's last |
| Outsole | <ul style="list-style-type: none">• PUR outsole, non-marking• Ergonomically designed tread |

| | | | | | | | | | | | | | | | | | |
|-----------------------------|---|----------|--------|----|----|-------|----|----|----|----------|-----------------------------|--|--|------|---------|--|--|
| | <ul style="list-style-type: none"> • Extremely flexible and excellent shock-absorption • Multi-layer-shock absorption system using dual density polyurethane for walking comfort • Excellent slip resistance • Self-cleaning tread • Resistant to oil and petrol • Withstands brief exposure to heat of approx. +120°C | | | | | | | | | | | | | | | | |
| Certificates | <ul style="list-style-type: none"> • Certified with uvex medicare for individual, orthopaedic inlay soles and individual adjustments of the sole unit such as overall increase, inside and outside increase and other solutions. | | | | | | | | | | | | | | | | |
| Areas of application | <ul style="list-style-type: none"> • Light applications | | | | | | | | | | | | | | | | |
| Technical data | <table> <tr> <td>Art.-No.</td> <td>6595.7</td> <td>.8</td> <td>.9</td> </tr> <tr> <td>Width</td> <td>10</td> <td>11</td> <td>12</td> </tr> <tr> <td>Standard</td> <td colspan="3">EN ISO 20347:2012 O1 FO SRC</td> </tr> <tr> <td>Size</td> <td colspan="3">35 – 52</td> </tr> </table> | Art.-No. | 6595.7 | .8 | .9 | Width | 10 | 11 | 12 | Standard | EN ISO 20347:2012 O1 FO SRC | | | Size | 35 – 52 | | |
| Art.-No. | 6595.7 | .8 | .9 | | | | | | | | | | | | | | |
| Width | 10 | 11 | 12 | | | | | | | | | | | | | | |
| Standard | EN ISO 20347:2012 O1 FO SRC | | | | | | | | | | | | | | | | |
| Size | 35 – 52 | | | | | | | | | | | | | | | | |
| Accessories | <p><i>uvex 1 sport nc climatic insole</i> (Article-No.: 9517.7 - .9)</p> <ul style="list-style-type: none"> • Provides the foot with exceptional, full-surface shock absorption and ensures comfort in high-strain zones • Ultra-breathable and moisture-absorbing materials • Shock absorption zones that assist natural movement • Non-irritating, comfortable surface structure <p><i>Laces</i></p> <ul style="list-style-type: none"> • Black (Article-No.: 8446.0 10) | | | | | | | | | | | | | | | | |