

Product Datasheet uvex 2 xenova 9504.1 - .3 S1 P SRC

**UVEX ARBEITSSCHUTZ GmbH, Würzburger Str. 181-189, D-90766 Fürth**

General features	<ul style="list-style-type: none">• Low weight and flexible S1 P safety sandal• Upper: microvelour• Suitable for people allergic to chrome as it's made from synthetic materials• All sole materials are free of silicones, plasticisers and other paint wetting impairment substances• Two adjustable hook-and-loop straps
Protection features	<ul style="list-style-type: none">• Meets ESD requirements: resistance to ground < 35 megaohm• 100% metal-free uvex xenova® toe cap. Compact design, anatomical shape, good lateral stability, no thermal conductivity properties• Metal-free, penetration-resistance insole in accordance with the latest standard, which does not impact shoe flexibility• Ergonomically designed outsole made from dual density polyurethane with excellent slip resistance
Comfort features	<ul style="list-style-type: none">• Light weight and optimised shock absorption• Outstanding wearer comfort results from a newly developed last and climate-optimised, breathable materials• Removable comfort insole, antistatic, with moisture control system and additional shock absorption in the heel and at the front of the foot• Soft padding on collar
Outsole	<ul style="list-style-type: none">• PUR outsole, non-marking• Ergonomically designed tread• Extremely flexible, excellent shock absorption• Unique PUR outsole system makes the shoe ultra-light

	<ul style="list-style-type: none">• Two-layer system with abrasion-resistant and cut-resistant outsole• Excellent slip resistance• Self-cleaning tread• Resistant to oil and petrol• Resistant to temperatures for short periods up to ca. +120°C																
Certificates	<ul style="list-style-type: none">• Certified with uvex medicare for individual, orthopaedic inlay soles and individual adjustments of the sole unit such as overall increase, inside and outside increase and other solutions.																
Areas of application	<ul style="list-style-type: none">• Moderate applications																
Technical data	<table><tr><td>Art.-no.</td><td>9504.1</td><td>.2</td><td>.3</td></tr><tr><td>Width</td><td>10</td><td>11</td><td>12</td></tr><tr><td>Standard</td><td colspan="3">EN ISO 20345:2011 S1 P SRC</td></tr><tr><td>Size</td><td colspan="3">38 – 52</td></tr></table>	Art.-no.	9504.1	.2	.3	Width	10	11	12	Standard	EN ISO 20345:2011 S1 P SRC			Size	38 – 52		
Art.-no.	9504.1	.2	.3														
Width	10	11	12														
Standard	EN ISO 20345:2011 S1 P SRC																
Size	38 – 52																
Accessories	<p><i>comfortable climatic insole</i> (Article-no.: 9534.7-9)</p> <ul style="list-style-type: none">• Provides the foot with exceptional, full-surface shock absorption and ensures comfort in high-strain zones• Ultra breathable and moisture-absorbing materials• Shock absorption zones that assist natural movement• Non-irritating, comfortable surface structure																